

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION	
NFPA Rating: Health-2; Flammability-3; Reactivity-0; Special: Manufacturers Name: D3 Industrial Products Inc Address: 7391 Heil Ave. Suite 101 Huntington Beach, CA 92647	HMIS Rating: Health-2; Flammability-3; Reactivity-0; Personal Protection-B DOT Hazard Classification: ORM-D Identity (trade name as used on label): D3 X20 Mist Adhesive
Date Prepared: 09/24/99 Prepared By: CKH Information Calls: 714-842-5522 EMERGENCY RESPONSE NUMBER: 1(800)255-3924	MSDS Number: 313 Revision- FIRST ISSUE NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	S A R A III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source "
CYCLOHEXANE	110-82-7	Yes	300	300	d
ACETONE	67-64-1	No	1000	750	d
ISOBUTANE/ PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d

SECTION 2 - PHYSICAUCHEMICAL CHARACTERISTICS	
Boiling Point: N/A	Specific Gravity (H2O.1): Concentrate Only 0.814
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.60	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A
Vapor Density (Air. 1): N/E	Evaporation Rate (1): N/E
Solubility in Water: Insoluble	Water Reactive: No
Appearance and Odor: Off-white conical mist, with acetone odor.	

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA		
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) EXTREMELY FLAMMABLE	Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E
FLASH POINT AND METHOD USED (non-aerosols): N/A EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.	SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. Use water fog to cool containers to prevent rupturing & exploding containers. Provide shielding for personnel.	
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.		

SECTION 4- REACTIVITY HAZARD DATA	
STABILITY <input checked="" type="checkbox"/> STABLE <input type="checkbox"/> UNSTABLE Incompatibility (Mat. to avoid): Strong oxidizing agents.	HAZARDOUS POLYMERIZATION <input type="checkbox"/> WILL <input checked="" type="checkbox"/> WILL NOT OCCUR Conditions to Avoid: Open flame, welding arcs, heat, sparks.
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide.	

SECTION 5- HEALTH HAZARD DATA	
PRIMARY ROUTES OF ENTRY: <input checked="" type="checkbox"/> INHALATION <input type="checkbox"/> INGESTION <input checked="" type="checkbox"/> SKIN ABSORPTION <input type="checkbox"/> EYE <input type="checkbox"/> NOT HAZARDOUS	

ACUTE EFFECTS Inhalation: Excessive inhalation of vapors can cause nasal & respiratory irritation, dizziness, weakness, nausea, headache, possible unconsciousness or asphyxiation. Eye Contact: Irritation. Skin Contact: Irritation due to defatting of skin. Ingestion: Possible chemical pneumonitis if aspirated into lungs.
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Aspiration into lungs may cause lung damage. Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.

EMERGENCY FIRST AID PROCEDURES
Eye Contact: Flush with plenty of water for at least 15 minutes. If irritated, seek medical attention. Skin Contact: Remove contaminated clothing and laundry before re-use. Wash affected areas with soap and water. If irritated, seek medical attention. Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention. Ingestion: DO NOT INDUCE VOMITING. Get immediate medical attention. NOTE TO PHYSICIAN: Gastric lavage using a cuffed endotracheal tube may be performed at your discretion.

SECTION 6- CONTROL AND PROTECTIVE MEASURES
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH in positive pressure mode. Protective Gloves: Neoprene. Eye Protection: Safety glasses recommended. Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV. Other Protective Clothing & Equipment: None Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.

SECTION 7- PRECAUTIONS FOR SAFE HANDLING AND USE
Steps To Be Taken If Material Is Spilled Or Released: Extinguish all ignition sources. Use positive pressure fresh air mask. Absorb spilled liquid with suitable medium. Place in closed container for proper disposal. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER. Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard. Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.

Other Precautions 84/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.
 We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.
 *Chemical Listed as Carcinogen or Potential Carcinogen [a] NTP [h] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only.